

TM65 Mid-Level Calculation **FTT-900**

Site name

Norfolk Bridge Works

27,560

Site address 11 Leveson Street, Sheffield, S4 7ER

Products per year

Assessment date	22/07/2022	Embodied carbon result with	
Assessor	Tasha Lyth	'mid-level TM65 calculation' method total:	
Organisation	Gripple Ltd		
Contact	sustainability@gripple.com	1.316 (kg CO ₂ e) ^{**}	

Type of product	MEP supports and bracketry
Capacity of equipment (M)	0.90 m
Product weight (kg)	0.27 kg
Material breakdown for at least 95% of the product weight (Y/N)	Y
Service life of the product (years)	25**
Types of refrigerant	N/A
Refrigerant GWP	0.00 kg
Energy consumption of the factory per unit of product (kWh)	0.10 kWh: Electricity, natural gas
Location of manufacture	Sheffield, UK
Product complexity	Category 1:

Product complexity Category 1: See CIBSE TM65 table 4.3



*Figure reached using 'Mid-Level' TM65 calculator

**Product service life when installed in accordance with Gripple key recommendations, 25 year extended product warranty available at Technical Services discretion.

www.gripple.com TM65-ENG-FTT-900

Gripple's policy is one of continuous development and innovation. We therefore reserve the right to alter specifications, etc. without notice.



Gripple Ltd | The Old West Gun Works | Savile Street East | Sheffield S4 7UQ Tel 0800 018 4264 Fax 0114 275 1155 Email sustainability@gripple.com

ĽK €€



TM65 Mid-Level Calculation FTT-900



Embodied carbon result with 'mid-level TM65 calculation' method total:

1.316 (kg CO₂e)*

Embodied carbon results breakdown (kg $CO_2^{}e$)		
A1: Material extraction	0.809 kg C0 ₂ e	TM65 assumption
A2: Transport	0.054 kg C0 ₂ e	TM65 assumption
A3: Manufacturing	0.025 kg C0 ₂ e	
A4: Transport to site	0.011 kg C0 ₂ e	TM65 assumption
B1: Use	0.000 kg C0 ₂ e	TM65 leakage type 0
B3: Repair	0.084 kg C0 ₂ e	TM65 assumption
C1: Deconstruction	0.000 kg C0 ₂ e	TM65 leakage type 0
C2: Transport	0.004 kg C0 ₂ e	
C3: Waste processing	0.025 kg C0 ₂ e	
C4: Disposal	0.001 kg C0 ₂ e	TM65 assumption

Embodied carbon results - without refrigerant leakage (kg CO ₂ e)			
A1-C4 (excluding B1,C1)	1.012 kg C0 ₂ e		
A1-C4 with Buffer Factor (excluding B1, C1)	1.316 kg C0 ₂ e		

Embodied carbon result - refrigerant leakage only (kg CO ₂ e)				
B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life)	0.000 kg C0 ₂ e			
Assumptions				
A1: Material carbon coefficient source	Source = CIBSE TM65 table 2.1			
B1: Refrigerant annual leakage rate (%)	0%: Source = CIBSE TM65 table 4.13 type 2			

100%: Source = CIBSE TM65 B3: Materials replaced as part of repair (%)

ĽK €€

50%: Source = CIBSE TM65 C4: Percentage of product going to landfill (%)

*Figure reached using 'Mid-Level' TM65 calculator **25 years for project work as decided by Gripple Technical Services

www.gripple.com

TM65-ENG-FTT-900



Gripple Ltd | The Old West Gun Works | Savile Street East | Sheffield S4 7UQ

Tel 0800 018 4264 Fax 0114 275 1155 Email sustainability@gripple.com