

TM65 Mid-Level Calculation SP2-LS-1MSS-F


Site name

Site address

Old West Gun Works

Savile Street East Sheffield, S9 7UQ

2,857 Products per year



Assessment date	11/08/2022	Embodied carbon result with 'mid-level TM65 calculation' method total:	
Assessor	Tasha Lyth		
Organisation	Gripple Ltd		
Contact	sustainability@gripple.com	0.145 (kg CO ₂ e)*	

Type of product	MEP supports and bracketry
Capacity of equipment (M)	1.0 m
Product weight (kg)	0.02 kg
Material breakdown for at least 95% of the product weight (Y/N)	Y
Service life of the product (years)	25**
Types of refrigerant	N/A
Refrigerant GWP	0.00 kg
Energy consumption of the factory per unit of product (kWh)	0.01 kWh: Electricity, natural gas
Location of manufacture	Sheffield, UK
Product complexity	Category 1:



*Figure reached using 'Mid-Level' TM65 calculator

**Product service life when installed in accordance with Gripple key recommendations, 25 year extended product warranty available at Technical Services discretion.

See CIBSE TM65 table 4.3

CE

www.gripple.com TM65-ENG-SP2-LS-1MSS-F

Gripple's policy is one of continuous development and innovation. We therefore reserve the right to alter specifications, etc. without notice.



Gripple Ltd | The Old West Gun Works | Savile Street East | Sheffield S4 7UQ Tel 0800 018 4264 Fax 0114 275 1155 Email sustainability@gripple.com



TM65 Mid-Level Calculation SP2-LS-1MSS-F

Embodied carbon result with 'mid-level TM65 calculation' method total:

0.145 (kg CO₂e)*

Embodied carbon results breakdown (kg CO ₂ e)		
A1: Material extraction	0.092 kg C0 ₂ e	TM65 assumption
A2: Transport	0.004 kg C0 ₂ e	TM65 assumption
A3: Manufacturing	0.002 kg C0 ₂ e	
A4: Transport to site	0.001 kg C0 ₂ e	TM65 assumption
B1: Use	0.000 kg C0 ₂ e	TM65 leakage type 0
B3: Repair	0.010 kg C0 ₂ e	TM65 assumption
C1: Deconstruction	0.000 kg C0 ₂ e	TM65 leakage type 0
C2: Transport	0.000 kg C0 ₂ e	
C3: Waste processing	0.002 kg C0 ₂ e	
C4: Disposal	0.000 kg C0 ₂ e	TM65 assumption

Embodied carbon results - without refrigerant leakage (kg CO ₂ e)			
A1-C4 (excluding B1,C1)	0.112 kg CO ₂ e		
A1-C4 with Buffer Factor (excluding B1, C1)	0.145 kg C0 ₂ e		

Embodied carbon result - refrigerant leakage only (kg CO ₂ e)			
B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life)	0.000 kg C0 ₂ e		
Assumptions			
A1: Material carbon coefficient source	Source = CIBSE TM65 table 2.1		
B1: Refrigerant annual leakage rate (%)	0%: Source = CIBSE TM65 table 4.13 type 2		
C1: Refrigerant end of life recovery rate (%)	100%: Source = CIBSE TM65 table 4.13 type 2		
B3: Materials replaced as part of repair (%)	10%: Source = CIBSE TM65		

50%: Source = CIBSE TM65 C4: Percentage of product going to landfill (%)

*Figure reached using 'Mid-Level' TM65 calculator **25 years for project work as decided by Gripple Technical Services

www.gripple.com TM65-ENG-SP2-LS-1MSS-F

Gripple's policy is one of continuous development and innovation. We therefore reserve the right to alter specifications, etc. without notice.



Tel 0800 018 4264 Fax 0114 275 1155 Email sustainability@gripple.com