

The Uni Wedge has been specifically designed as a single universal fixing suitable for the seven most popular decking profiles available in the UK.

ADVANTAGES

- One fixing suits seven most popular decking profiles
- Single piece construction
- Allows for manufacturing tolerances in the decking profile
- Separate fixing screw to ease final adjustment
- M6, M8 and M10 threaded fixing holes
- Requires no site power or skilled labour

PRODUCT INFORMATION

- Load rated at 100kg, with a 3:1 safety factor
- To secure the installation both the screw (in position 1 or 2) and the threaded Stud must be tightened into the decking profile



INSTALLATION

<p>1) Manually insert the screw into the desired position (see table)</p>	<p>2) Insert wedge nut into decking channel and rotate 90°</p>	<p>3) Tighten the screw into the decking profile, using an allen key</p>	<p>4) Insert Stud hanger into the wedge, ensuring it is tightened into the decking</p>

DECKING PROFILES

Decking Manufacturer	Decking Type	Screw Position	Tightening Torque (Nm) <i>Use 4mm Hexagon key to tighten grubscrew</i>
KINGSPAN	Multideck 60	1	8
	Multideck 80	1	8
RICHARD LEES	Ribdeck 80	1	8
	Ribdeck AL	1	8
	Ribdeck E60	1	8
SMD	TR60	2	8
	TR80	2	8

IMPORTANT INFORMATION

1. Construction materials and conditions vary on different sites. If it is suspected that the base material has insufficient strength to achieve a suitable fixing, contact Gripple Ltd. The responsibility for judgement of base material strength lies with the installer, and not with Gripple Ltd.
2. The information and recommendations given herein are believed to be correct at time of writing. The data has been obtained from tests done under laboratory, or other controlled conditions and it is the users responsibility to use the data given in light of conditions on site, taking account of the intended use of the products concerned.
3. Whilst Gripple Ltd can give general guidance and advice, the nature of Gripple products means that the ultimate responsibility for selecting the correct product for a particular application must lie with the customer.
4. All products must be used, handled and applied in accordance with current product instructions and manufacturers recommendations for use, published by Gripple Ltd.
5. Gripple's policy is one of continuous development and innovation. We therefore reserve the right to alter specifications, etc. without notice.