

# Pipe Insulation

## Armaflex Pipe Collars

**Thermally efficient** - CFC/HCFC-free insulation with thermal conductivities as low as 0.036 W/mK

**Space saving** - advantageous in confined spaces or where space is at a premium

**High performance** - reduces heat loss and highly moisture resistant


**Lighter** - combined with the Gripple Clamp - pipe supports can be placed up to 2 m apart, achieving a 75 kg load rating with a significant 5:1 safety factor




## Notes

- For Armaflex Pipe Collars, insulation thickness options are 15, 25 or 32 mm. Armaflex is manufactured by Armacell
- Gripple Universal Clamps can be used with Armaflex insulation. Clamps sold separately
- Steel and copper pipes not supplied with any Pipe Collars

## Armaflex Pipe Collar (for steel pipes)

Product information	Product code	Pipe size OD (mm)	Insulation thickness
	GAF-PS-21-15	21	15 mm
	GAF-PS-27-15	27	15 mm
	GAF-PS-34-15	34	15 mm
	GAF-PS-42-15	42	15 mm
	GAF-PS-21-25	21	25 mm
	GAF-PS-27-25	27	25 mm
	GAF-PS-34-25	34	25 mm
	GAF-PS-42-25	42	25 mm
	GAF-PS-21-32	21	32 mm
	GAF-PS-27-32	27	32 mm
	GAF-PS-34-32	34	32 mm
	GAF-PS-42-32	42	32 mm
	GAF-PS-48-15	48	15 mm
	GAF-PS-60-15	60	15 mm
	GAF-PS-76-15	76	15 mm
	GAF-PS-89-15	89	15 mm
	GAF-PS-48-25	48	25 mm
	GAF-PS-60-25	60	25 mm
	GAF-PS-76-25	76	25 mm
	GAF-PS-89-25	89	25 mm
GAF-PS-48-32	48	32 mm	
GAF-PS-60-32	60	32 mm	
GAF-PS-76-32	76	32 mm	
GAF-PS-89-32	89	32 mm	

## Armaflex Pipe Collar (for copper pipes)

Product information	Product code	Pipe size OD (mm)	Insulation thickness
	GAF-PS-15-15	15	15 mm
	GAF-PS-22-15	22	15 mm
	GAF-PS-28-15	28	15 mm
	GAF-PS-35-15	35	15 mm
	GAF-PS-42-15	42	15 mm
	GAF-PS-54-15	54	15 mm
	GAF-PS-67-15	67	15 mm
	GAF-PS-76-15	76	15 mm
	GAF-PS-15-25	15	25 mm
	GAF-PS-22-25	22	25 mm
	GAF-PS-28-25	28	25 mm
	GAF-PS-35-25	35	25 mm
	GAF-PS-42-25	42	25 mm
	GAF-PS-54-25	54	25 mm
	GAF-PS-67-25	67	25 mm
	GAF-PS-76-25	76	25 mm
	GAF-PS-15-32	15	32 mm
	GAF-PS-22-32	22	32 mm
	GAF-PS-28-32	28	32 mm
	GAF-PS-35-32	35	32 mm
	GAF-PS-42-32	42	32 mm
	GAF-PS-54-32	54	32 mm
	GAF-PS-67-32	67	32 mm
	GAF-PS-76-32	76	32 mm