

Catenary Kit & C-Clip

Create secure overhead spans by running high strength wire rope between two fixing points. Ideal for applications where no direct vertical anchor point is available.

Versatile - can easily be used for a variety of applications including lighting, HVAC, pipework and electrical containment

Quick - fewer components compared to traditional methods, up to six times faster to install than traditional suspension systems

Aesthetic - the design complements enclosed and open soffit spaces providing a discreet finish

Safe - no "Hot Works" permit required for installation, improving health and safety on-site

Easily tensioned - using the Gripple Catenary Tensioning Tool reducing time spent working at height




Secure - locking mechanism in the Lockable Plus prevents dynamic movements

Strong - industry approved

Lightweight - easy to move and handle on-site, whilst reducing the load on the building structure



| Product information / size | | Product code | Length (m) | Order Quantity |
|---|--------------------|-------------------|------------|----------------|
| CATENARY KIT 3 MM  | 3 mm 30 kg | CTI-3MM-3M | 3 | 1 |
| | | CTI-3MM-5M | 5 | 1 |
| | | CTI-3MM-8M | 8 | 1 |
| | | CTI-3MM-10M | 10 | 1 |
| | | CTI-3MM-20M | 20 | 1 |
| | | CTI-3MM-30M | 30 | 1 |
| | | CTI-3MM-40M | 40 | 1 |
| CATENARY KIT 6 MM  | 6 mm 100 kg | CTI-6MM-3M | 3 | 1 |
| | | CTI-6MM-5M | 5 | 1 |
| | | CTI-6MM-8M | 8 | 1 |
| | | CTI-6MM-10M | 10 | 1 |
| | | CTI-6MM-20M | 20 | 1 |
| | | CTI-6MM-30M | 30 | 1 |
| | | CTI-6MM-40M | 40 | 1 |
| CATENARY WALL BRACKET  | | CAT-BRACKET-100MM | - | - |

| Product information / size | | Product code | Length (m) | Order Quantity |
|--|---------------|------------------------------|------------|----------------|
| C-CLIP (3 MM) | | HF1-CC3-1M | 1 | 10 |
|  | 3 mm 10 kg | HF1-CC3-2M | 2 | 10 |
| | | HF1-CC3-3M | 3 | 10 |
| | | HF1-CC3-4M | 4 | 10 |
| | | HF1-CC3-5M | 5 | 10 |
| | | HF1-CC3-8M | 8 | 10 |
| | | HF1-CC3-10M | 10 | 10 |
| | | C-CLIP (6 MM) | | HF2-CC6-1M |
|  | 6 mm 45 kg | HF2-CC6-2M | 2 | 10 |
| | | HF2-CC6-3M | 3 | 10 |
| | | HF2-CC6-4M | 4 | 10 |
| | | HF2-CC6-5M | 5 | 10 |
| | | HF2-CC6-8M | 8 | 10 |
| | | HF2-CC6-10M | 10 | 10 |
| | | C-CLIP SUPPLIED LOOSE | | |
|  | | CCLIP-3MM-BB | | |
| | | CCLIP-3MM-2PIN-BB | | |
| | | CCLIP-6MM-BB | | |
| | | CCLIP-6MM-2PIN-BB | | |