

# Clamps & Brackets

## Universal Bracket



Designed for quick and easy support of electrical containment, pipework and other mechanical services.

- **Quick** – pre-cut lengths eliminate the need for cutting channel-on-site, allowing more productive use of labour
- **Versatile** – can be bolted directly to soffit or wall, or suspended from the soffit using a Gripple Hanger
- **Compatible** – uniform slots on three sides allow accurate alignment of Gripple clamps and QT accessories with the fourth side permitting the use of channel / strut accessories
- **Safe** – improved health and safety as no tools or 'hot works' permit required for installation
- **Flexible** – perfect for multi-service installations, using multiple hangers
- **Approved** – fire tested by Exova to F120

Product information / size	Product code	Length (mm)	Order Quantity
UNIVERSAL BRACKET 170 MM NO CLAMPS	UB-170	235	5
UNIVERSAL BRACKET 270 MM NO CLAMPS	UB-270	335	5
UNIVERSAL BRACKET 370 MM NO CLAMPS	UB-370	435	5
UNIVERSAL BRACKET 470 MM NO CLAMPS	UB-470	535	5
UNIVERSAL BRACKET 570 MM NO CLAMPS	UB-570	635	5
UNIVERSAL BRACKET 670 MM NO CLAMPS	UB-670	735	5
UNIVERSAL BRACKET 770 MM NO CLAMPS	UB-770	835	5
UNIVERSAL BRACKET 870 MM NO CLAMPS	UB-870	935	5
UNIVERSAL BRACKET 970 MM NO CLAMPS	UB-970	1035	5
UNIVERSAL BRACKET 1070 MM NO CLAMPS	UB-1070	1135	5
UNIVERSAL BRACKET 1170 MM NO CLAMPS	UB-1170	1235	5
UNIVERSAL BRACKET 1270 MM NO CLAMPS	UB-1270	1335	5
UNIVERSAL BRACKET 1370 MM NO CLAMPS	UB-1370	1435	5
UNIVERSAL BRACKET 1470 MM NO CLAMPS	UB-1470	1535	5

Product information / size	Product code	Length (mm)	Order amount
UNIVERSAL BRACKET END CAP	UB-ENDCAP-100PK	41.5mm	100

# Low Profile Bracket

Supplied with QT Compact Clamps for quick and easy support of pipework within mechanical and plumbing services.



**Quick** – pre-cut lengths eliminating the need for cutting channel on-site, allowing more productive use of labour

**Versatile** – can be bolted directly to soffit or wall with less than 15 mm depth

**Compatible** – brackets are supplied with QT Universal Clamps or QT Compact Clamps featuring quarter turn fixing

**Safe** – improved health and safety as no tools or “Hot Works” permit required for installation

**Strong** – 150 kg load rating in sizes ranging from 250 mm to 1250 mm

Product information / size	Product code	Length (mm)	Order amount
LOW PROFILE BRACKET 180 MM NO CLAMPS	LPB180	180	10
LOW PROFILE BRACKET 250 MM NO CLAMPS	LPB250	250	10
LOW PROFILE BRACKET 350 MM NO CLAMPS	LPB350	350	10
LOW PROFILE BRACKET 450 MM NO CLAMPS	LPB450	450	10
LOW PROFILE BRACKET 550 MM NO CLAMPS	LPB550	550	10
LOW PROFILE BRACKET 650 MM NO CLAMPS	LPB650	650	10
LOW PROFILE BRACKET 750 MM NO CLAMPS	LPB750	750	10
LOW PROFILE BRACKET 850 MM NO CLAMPS	LPB850	850	10
LOW PROFILE BRACKET 950 MM NO CLAMPS	LPB950	950	10
LOW PROFILE BRACKET 1050 MM NO CLAMPS	LPB1050	1050	10
LOW PROFILE BRACKET 1150 MM NO CLAMPS	LPB1150	1150	10
LOW PROFILE BRACKET 1250 MM NO CLAMPS	LPB1250	1250	10
LOW PROFILE BRACKET 1350 MM NO CLAMPS	LPB1350	1350	10
LOW PROFILE BRACKET 1450 MM NO CLAMPS	LPB1450	1450	10
LOW PROFILE BRACKET 1550 MM NO CLAMPS	LPB1550	1550	10

# QT Universal Clamp

Designed for use with Gripple Brackets to provide quick and easy pipework installation.

**Quick** – up to ten times faster than traditional methods due to integral mounting pillar and quarter turn attachment to Universal Bracket

**Simple** – no tools required for installation

**Universal** – replaces more than 13 different pipe rings from OD1 (15mm copper) to OD114 (4" steel)

**Robust** – retractable sleeve, pre-fitted to wire rope to prevent galvanic corrosion

**Versatile** – a variety of rubber pads provide insulation against vibration (noise reduction > 23 db)

**Strong** – 75 kg SWL with a 3:1 safety factor (equivalent to OD 89 (3" steel) filled with water)

**Compatible** – available with Kooltherm/Armaflex pipe collars for insulated pipe

**Safe** – supplied in ready-to-use kits with Gripple Brackets, for easy site storage & waste reduction



Product information / size	Product code	Length (mm)	Order amount
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 400 MM STANDARD PAD	GC2-T-400MM	400	10
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 600 MM STANDARD PAD	GC2-T-600MM	600	10
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 400 MM WIRE LARGE PAD	GC2-T-400MM-L	400	10
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 600 MM WIRE LARGE PAD	GC2-T-600MM-L	600	10
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 400 MM WIRE ACOUSTIC PAD	GC2-T-400MM-A	400	10
GRIPPLE UNIVERSAL CLAMP INS QT CONNECTION 45 KG 600 MM WIRE ACOUSTIC PAD	GC2-T-600MM-A	600	10

# QT Compact Clamp

Used in conjunction with Gripple Brackets for quick and easy support of all types of pipework within mechanical and plumbing services.

**Quick** – up to ten times faster than traditional methods due to integral mounting pillar and quarter turn attachment to Gripple Brackets

**Simple** – no tools required for installation

**Universal** – replaces more than 13 different pipe rings from OD15 (15 mm copper) to OD114 (4" steel)

**Robust** – retractable sleeve, pre-fitted to wire rope to prevent galvanic corrosion

**Versatile** – a variety of rubber pads provide insulation against vibration (noise reduction > 23 db)

**Strong** – 75 kg SWL with a 3:1 safety factor (equivalent to OD 89 (3" steel) filled with water)

**Compatible** – available with Kooltherm/Armaflex pipe collars for insulated pipe

**Safe** – supplied in ready-to-use kits with Gripple Brackets, for easy site storage and waste reduction



Product information / size	Product code	Length (mm)	Order amount
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 400 MM WIRE STANDARD PAD	GC2-C-400MM	400	10
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 600 MM WIRE STANDARD PAD	GC2-C-600MM	600	10
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 400 MM WIRE LARGE PAD	GC2-C-400MM-L	400	10
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 600 MM WIRE LARGE PAD	GC2-C-600MM-L	600	10
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 400 MM WIRE ACOUSTIC PAD	GC2-C-400MM-A	400	10
GRIPPLE UNIVERSAL CLAMP INS COMPACT CONNECTION 45 KG 600 MM WIRE ACOUSTIC PAD	GC2-C-600MM-A	600	10

# Universal Clamp

Designed for use with Gripple Brackets to provide quick and easy installation of pipe and duct.

**Flexible** – M8/M10 dual thread allows for flexible attachment to Gripple brackets, channel and rod

**Universal** – replaces more than 13 different pipe rings from OD15 (15 mm copper) to OD114 (4" steel)

**Robust** – retractable sleeve, pre-fitted to wire rope to prevent galvanic corrosion

**Versatile** – a variety of rubber pads provide insulation against vibration (noise reduction > 23 db)

**Strong** – 75 kg SWL with a 3:1 safety factor (equivalent to OD 89 (3" steel) filled with water)

**Compatible** – available with Kooltherm/Armaflex pipe collars for insulated pipe



## - For Pipework

Product information / size	Product code	Length (mm)	Order amount
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 400 MM WIRE STANDARD PAD	GC2-INS-M8-M10-400MM	400	10
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 600 MM WIRE STANDARD PAD	GC2-INS-M8-M10-600MM	600	10
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 400 MM WIRE LARGE PAD	GC2-INS-M8-M10-400MM-L	400	10
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 600 MM WIRE LARGE PAD	GC2-INS-M8-M10-600MM-L	600	10
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 400 MM WIRE ACOUSTIC PAD	GC2-INS-M8-M10-400MM-A	400	10
GRIPPLE UNIVERSAL CLAMP M8/M10 THREAD 45 KG 600 MM WIRE ACOUSTIC PAD	GC2-INS-M8-M10-600MM-A	600	10

## - For Ductwork

Product information / size	Product code	Length (m)	Order amount
GRIPPLE UNIVERSAL CLAMP FOR DUCT M8/M10 THREAD 1.5 M WIRE STANDARD PAD	GC2-PAD-M8-M10-1.5M	1.5	10
GRIPPLE UNIVERSAL CLAMP FOR DUCT M8/M10 THREAD 2.5 M WIRE STANDARD PAD	GC2-PAD-M8-M10-2.5M	2.5	10
GRIPPLE UNIVERSAL CLAMP FOR DUCT M8/M10 THREAD 1.5 M WIRE LARGE PAD	GC2-PAD-M8-M10-1.5M-L	1.5	10
GRIPPLE UNIVERSAL CLAMP FOR DUCT M8/M10 THREAD 2.5 M WIRE LARGE PAD	GC2-PAD-M8-M10-2.5M-L	2.5	10

# Height Adjustable Universal Clamp

Used in conjunction with Gripple Brackets for quick and easy support of all types of pipework within mechanical and plumbing services.



**Quick** – up to ten times faster than traditional methods due to integral mounting pillar and quarter turn attachment to Gripple Brackets

**Simple** – no tools required for installation

**Universal** – replaces more than 13 different pipe rings

**Robust** – retractable sleeve, pre-fitted to wire rope to prevent galvanic corrosion

**Versatile** – a variety of rubber pads provide insulation against vibration (noise reduction > 23 db)

**Strong** – 75 kg SWL with a 3:1 safety factor (equivalent to OD 89 (3" steel) filled with water)

**Compatible** – available with Kooltherm/Armaflex pipe collars for insulated pipe

**Safe** – supplied in ready-to-use kits with Gripple Brackets

Product information / size	Product code	Length (m)	Order amount
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 400 MM STANDARD PAD	GC2-HA100-INS-M8-400MM	400	10
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 600 MM STANDARD PAD	GC2-HA100-INS-M8-600MM	600	10
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 400 MM WIRE LARGE PAD	GC2-HA100-INS-M8-400MM-L	400	10
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 600 MM WIRE LARGE PAD	GC2-HA100-INS-M8-600MM-L	600	10
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 400 MM WIRE ACOUSTIC PAD	GC2-HA100-INS-M8-400MM-A	400	10
GRIPPLE HEIGHT ADJUSTABLE CLAMP M8/M10 THREAD 45 KG 600 MM WIRE ACOUSTIC PAD	GC2-HA100-INS-M8-600MM-A	600	10

Product information / size	Product code	Length (mm)	Order amount
QT ACCESSORY FOR GRIPPLE UNIVERSAL CLAMP (ACCESSORY & M8 NUT ONLY)	GC2-QTA-M8	100	10

## GCS (Gripple Clamp for Strut)

Versatile pipe clamp solution designed for use with standard strut channel profiles to secure up to 225 mm O.D. piping systems in multiple applications.

**Quick** – simple and secure attachment to channel with a 5 mm hex key

**Universal** – secures up to 225 mm O.D piping systems, eliminating the need to stock multiple pipe clamps

**Versatile** – suitable for mechanical piping and plumbing applications including HVAC refrigerant piping, VRF systems, medical gas and domestic water

**Strong** – can be used to rack piping (refer to strut manufacturer for point loads) or suspend from the strut with a 75 kg safe working load per clamp

**Robust** – secure fit to strut using the hex key allows safe transit of pre-built racks from off-site prefabrication shop to the job site

**Safe** – stainless steel securing strap with non-conductive coating to prevent galvanic corrosion between dissimilar metals

**Adjustable** – prior to final lock, button release allows easy adjustment or addition of insulation after installation



Product information / size	Product code	Length (mm)	Order amount
GRIPPLE CLAMP FOR STRUT WITH 850MM STRAP + ALLEN KEY	GCS-30-30BL	850	10
GRIPPLE CLAMP FOR STRUT SMALL PIPE CLIP	GCS-SP-CLIP		10

## Pipework Accessory - Spreader Band

A plastic spreader band for attachment to Gripple No.2 and No.3 wire, for spreading the load of various suspended services.



Product information / size	Product code	Length (mm)	Order amount
SPREADER BAND (BLACK)	SPREADER-BAND	N/A	1
SPREADER BAND (BLACK) - BULK	SPREADER-BAND-BULK	N/A	1

## Pipework Accessory - Beam Clamps

Designed for use with Gripple Universal Brackets for fixing directly to steel I-Beams.



Product information / size	Product code	Length (mm)	Order amount
PAIR OF BEAM CLAMPS FOR UNIVERSAL BRACKETS	PB-BEAM-CLAMPS-2P	N/A	1
SINGLE BEAM CLAMP FOR UNIVERSAL BRACKETS	PB-BEAM-CLAMP	N/A	1