

Pipe Insulation

KoolTherm Pipe Collars

Thermally efficient - CFC/HCFC-free insulation with thermal conductivities as low as 0.021 W/mK

Space saving - advantageous in confined spaces or where space is at a premium

High performance - reduces heat loss and highly moisture resistant

Lighter - combined with the Gripple Clamp - pipe supports can be placed up to 2 m apart, achieving a 75 kg load rating with a significant 5:1 safety factor



Notes



- For KoolTherm, insulation thickness options are 15, 20, 25, 30 or 40 mm. KoolTherm is manufactured by Kingspan
- Gripple Universal Clamps can be used with KoolTherm insulation. Clamps sold separately
- Steel and copper pipes not supplied with any Pipe Collars

KoolTherm Collar (for steel pipes)

Product information	Product code	Pipe size OD (mm)	Insulation thickness
	GKT-PS-21-15	21	15 mm
	GKT-PS-27-15	27	15 mm
	GKT-PS-34-15	34	15 mm
	GKT-PS-42-15	42	15 mm
	GKT-PS-21-20	21	20 mm
	GKT-PS-27-20	27	20 mm
	GKT-PS-34-20	34	20 mm
	GKT-PS-42-20	42	20 mm
	GKT-PS-21-25	21	25 mm
	GKT-PS-27-25	27	25 mm
	GKT-PS-34-25	34	25 mm
	GKT-PS-42-25	42	25 mm
	GKT-PS-21-30	21	30 mm
	GKT-PS-27-30	27	30 mm
	GKT-PS-34-30	34	30 mm
	GKT-PS-42-30	42	30 mm
	GKT-PS-21-40	21	40 mm
	GKT-PS-27-40	27	40 mm
	GKT-PS-34-40	34	40 mm
	GKT-PS-42-40	42	40 mm
	GKT-PS-48-15	48	15 mm
	GKT-PS-60-15	60	15 mm
	GKT-PS-76-15	76	15 mm
	GKT-PS-89-15	89	15 mm
	GKT-PS-48-20	48	20 mm
	GKT-PS-60-20	60	20 mm
	GKT-PS-76-20	76	20 mm
	GKT-PS-89-20	89	20 mm
	GKT-PS-48-25	48	25 mm
	GKT-PS-60-25	60	25 mm
	GKT-PS-76-25	76	25 mm
	GKT-PS-89-25	89	25 mm
	GKT-PS-48-30	48	30 mm
	GKT-PS-60-30	60	30 mm
	GKT-PS-76-30	76	30 mm
	GKT-PS-89-30	89	30 mm
	GKT-PS-48-40	48	40 mm
	GKT-PS-60-40	60	40 mm
	GKT-PS-76-40	76	40 mm
	GKT-PS-89-40	89	40 mm



KoolTherm Collar (for copper pipes)

Product information	Product code	Pipe size OD (mm)	Insulation thickness
 	GKT-PS-15-15	15	15 mm
	GKT-PS-22-15	22	15 mm
	GKT-PS-28-15	28	15 mm
	GKT-PS-35-15	35	15 mm
	GKT-PS-42-15	42	15 mm
	GKT-PS-54-15	54	15 mm
	GKT-PS-67-15	67	15 mm
	GKT-PS-76-15	76	15 mm
	GKT-PS-15-20	15	20 mm
	GKT-PS-22-20	22	20 mm
	GKT-PS-28-20	28	20 mm
	GKT-PS-35-20	35	20 mm
	GKT-PS-42-20	42	20 mm
	GKT-PS-54-20	54	20 mm
	GKT-PS-67-20	67	20 mm
	GKT-PS-76-20	76	20 mm
	GKT-PS-15-25	15	25 mm
	GKT-PS-22-25	22	25 mm
	GKT-PS-28-25	28	25 mm
	GKT-PS-35-25	35	25 mm
	GKT-PS-42-25	42	25 mm
	GKT-PS-54-25	54	25 mm
	GKT-PS-67-25	67	25 mm
	GKT-PS-76-25	76	25 mm
	GKT-PS-15-30	15	30 mm
	GKT-PS-22-30	22	30 mm
	GKT-PS-28-30	28	30 mm
	GKT-PS-35-30	35	30 mm
	GKT-PS-42-30	42	30 mm
	GKT-PS-54-30	54	30 mm
	GKT-PS-67-30	67	30 mm
	GKT-PS-76-30	76	30 mm
GKT-PS-15-40	15	40 mm	
GKT-PS-22-40	22	40 mm	
GKT-PS-28-40	28	40 mm	
GKT-PS-35-40	35	40 mm	
GKT-PS-42-40	42	40 mm	
GKT-PS-54-40	54	40 mm	
GKT-PS-67-40	67	40 mm	
GKT-PS-76-40	76	40 mm	